



# Nut Splitter

## Hydraulic Nut Splitter

The HYTORC Nut Splitter range of tools has been developed to assist in the removal of corroded, seized or damaged nuts. The Nut Splitter tools have a shrouded cutting head to contain the split nut and have been developed to increase the access to tight flange joints. The tools have no exposed finger pinch points and are supplied with a swivel handle and a safety lanyard as standard. The Nut Splitter is powered by a 10,000 psi pump.

### **HYT-104-110HYD Hydraulic Nut Splitter**

---

#### **KIT CONTENTS:**

- 1 x HYT-104-110HYD Nut Splitter
- 1 x Spare Cutting Tip
- 1 x Spare Tip Retention Screw
- 1 x Spare Alignment Screw
- 1 x Set of Hex Keys
- 1 x Safety Lanyard
- 1 x Instruction Manual
- 1 x Carry Case



## Technical Data



**Tool Weight:** 23.4 lb (10.6 kg)

**Gross Weight:** 30.0 lb (13.6 kg)

**Carry Case Dimensions:**

22.8" x 13.8" x 7.9"

(580 mm x 350 mm x 200 mm)

**Minimum Pump Oil Capacity:**

14.04 in<sup>3</sup> (230 cc)

## Range of Application

Nut Splitter	Hex Nut A/F	Metric (Coarse)	UNC (Standard)	UNC (Heavy)
HYT-008-010HYD	0.69" - 1.18" (17.5 mm - 30.0 mm)	M12 - M20	9/16" - 5/8"	1/2" - 5/8"
HYT-009-014HYD	0.91" - 1.44" (23.0 mm - 36.5 mm)	M16 - M22	5/8" - 7/8"	9/16" - 7/8"
HYT-014-102HYD	1.26" - 2.01" (32.0 mm - 51.0 mm)	M24 - M30	1" - 1 1/4"	7/8" - 1 1/8"
HYT-104-110HYD	2.00" - 2.56" (50.8 mm - 65.0 mm)	M33 - M42	1 3/8" - 1 5/8"	1 1/4" - 1 5/8"
HYT-110-200HYD	2.56" - 3.15" (65.0 mm - 80.0 mm)	M45 - M52	1 3/4" - 2"	1 5/8" - 2"
HYT-200-208HYD	3.13" - 3.94" (79.4 mm - 100.0 mm)	M56 - M68	2 1/4" - 2 1/2"	2" - 2 1/2"
HYD-208-300HYD	3.87" - 4.53" (98.4 mm - 115.0 mm)	M72 - M80	2 3/4" - 3"	2 1/2" - 3"

## Contact Information

333 RT. 17 North  
Mahwah, NJ 07430

1-800-FOR-HYTORC  
www.hytorc.com

**HYTORC**  
Since 1968