



PUMP SPECIFICATIONS AND FEATURES

Power	115v and 230v	
Data Recording	Optional	
Gauge	(Not necessary but can be attached to the side of the valve block.)	
Reservoir Capacity	.7 gals. / 2.7 l	
Stages	3	
Weight	48 lbs. / 22 kg (Manual) 52 lbs. / 23 kg (Automatic)	
Maximum Oil Flow Rate	50 Hz 580 PSI 40 bar	60 Hz 330 cu. in./min. 4.05 l/min.
Middle Oil Flow Rate	50 Hz 2,175 PSI 150 bar	60 Hz 91 cu. in./min. 1.5 l/min.
High Oil Flow Rate	50 Hz 10,000 PSI 700 bar	60 Hz 31 cu. in./min. 0.5 l/min.
15' Remote control	Yes	
15' Twin Line Steel Braided Hydraulic Hose	Yes	

COMPLETE KIT CONTENTS

- VECTOR MINI Pump
- 15' Twin Line Hose
- 1 gallon / 3.8 l of oil

HYTORC owns all content, copyrights, trademarks and patents in this document. © 2020 HYTORC. Any unauthorized use or distribution of any material from this document is strictly prohibited.



Headquarters:
333 Route 17 N., Mahwah, NJ 07430
+1-201-512-9500

Email:
info@hytorc.com

Phone:
1-800-FOR-HYTORC

Online:
hytorc.com