

American National Standard Flange SPECIFICATIONS				Torque Chart for ASTM A193 Grade B7 Studs In Ft./Lbs At 50% Of Yield Add .04 to the u to = K factor					
900 lb				Moly Lube u=0.085 K=.0125	Nickel Lube u=0.110 K=.150	Copper Lube u=0.100 K=.140	Machine Oil u=0.160 K=.200	Dry Torque u=0.400 K=.440	Tool Model
PIPE SIZE	BOLT DIA.	# OF BOLTS	HEAVY HEX A/F						
1/2"	3/4"	4	1-1/4"	137	154	165	219	483	Versa-1
3/4"	3/4"	4	1-1/4"	137	154	165	219	483	Versa-1
1"	7/8"	4	1-7/16"	221	265	247	353	777	Versa-1
1-1/4"	7/8"	4	1-7/16"	221	265	247	353	777	Versa-1
1-1/2"	1"	4	1-5/8"	331	397	371	530	1165	Versa-1
2"	7/8"	8	1-7/16"	221	265	247	353	777	Versa-1
2-1/2"	1"	8	1-5/8"	331	397	371	530	1165	Versa-1
3"	7/8"	8	1-7/16"	221	265	247	353	777	Versa-1
3-1/2"	N/A	N/A	N/A						
4"	1-1/8"	8	1-13/16"	486	583	544	778	1711	Stealth-2
5"	1-1/4"	8	2"	683	820	765	1093	2404	Stealth-2
6"	1-1/8"	12	1-13/16"	486	583	544	778	1711	Stealth-2
8"	1-3/8"	12	2-3/16"	927	1112	1038	1483	3263	Stealth-4
10"	1-3/8"	16	2-3/16"	927	1112	1038	1483	3263	Stealth-4
12"	1-3/8"	20	2-3/16"	927	1112	1038	1483	3263	Stealth-4
14"	1-1/2"	20	2-3/8"	1223	1468	1370	1957	4306	Stealth-4
16"	1-5/8"	20	2-9/16"	1576	1892	1766	2522	5549	Stealth-4
18"	1-7/8"	20	2-15/16"	2474	2969	2771	3959	8709	Stealth-8
20"	2"	20	3-1/8"	3029	3635	3392	4846	10662	Stealth-8
24"	2-1/2"	20	3-7/8"	5492	6590	6151	8787	19332	Stealth-14
26"	2-3/4"	20	4-1/4"	7378	8854	8263	11805	25971	Stealth-22
28"	3"	20	4-5/8"	9653	11584	10811	15445	33978	Stealth-36
30"	3"	20	4-5/8"	9653	11584	10811	15445	33978	Stealth-36
32"	3-1/4"	20	5"	12353	14823	13835	19765	43482	Stealth-36
34"	3-1/2"	20	5-3/8"	15514	18617	17376	24823	54611	Stealth-36
36"	3-1/2"	20	5-3/8"	15514	18617	17376	24823	54611	Stealth-36
38"	3-1/2"	32	5-3/8"	15514	18617	17376	24832	54611	Stealth-36

40"	3-1/2"	36	5-3/8"	15514	18617	17376	24823	54611	Stealth-36
42"	3-1/2"	36	5-3/8"	15514	18617	17376	24832	54611	Stealth-36
44"	3-3/4"	40	5-3/4"	19174	23009	21475	30678	67492	
46"	4"	40	6-1/8"	23368	28041	26172	37388	82254	
48"	4"	44	6-1/8"	23368	28041	26172	37388	82254	
50"	N/A	N/A	N/A						
52"	N/A	N/A	N/A						
54"	N/A	N/A	N/A						
56"	N/A	N/A	N/A						
58"	N/A	N/A	N/A						
60"	N/A	N/A	N/A						

This spread sheet is to be used as a guide. all results should be analyzed against actual field results to establish their validity.